FILASTONE PLUS



COLOUR-ENHANCING STAIN PROTECTOR SOLVENT-BASED



POLISHED

NATURAL STONES

AND AGGLOMERATES

UNPOLISHED NATURAL
STONES AND
AGGLOMERATES



WHAT IT'S FOR

- Protects and enhances the original colour of polished, honed, rough and tumbled natural stone.
- Penetrates deeply into the material, protecting it from water and oily stains and dirt.
- Ideal for windowsills, tops, rosettes, inset decorations. Perfect for interior and exterior surfaces.

ADVANTAGES

- Intensifies colour whatever the surface finish.
- For interior and exterior surfaces.
- Non-yellowing, UV resistant, provides long-lasting protection.
- Very high coverage rates.
- Eliminates weaknesses in granite.
- No film forming.
- Certified as suitable for use on food contact surfaces.

HOW IT'S USED

No dilution: ready to use.

Application:

- Using a paintbrush, a sponge or other applicator, apply FILASTONEPLUS to a clean, dry surface.
- During the application rub the surface with a sponge or a cloth to help the penetration of the product and the removal af any excess.
- The surface can be walked on after only eight hours.
- 4.For a deeper colour, repeat procedure, waiting at least 8 hours between each application.

Maintenance:

diluted solution of FILACLEANER.

Caution:

Once treated with FILASTONE PLUS, your stone cannot be returned to its original state. Perform a preliminary spot test on a small area to view the effect.

COVERAGE

With one litre:

Polished stone 30/50m² Rustic stone 15/25m²

"Coverage rates are approximate and refer to a single coat of the product"

Packaging

250ml cans in box of 12. 1 litre cans in box of 12. 5 litre cans in box of 4.

PRECAUTIONS

- Keep out of the reach of children.
- Dispose of the container properly after use.
- Solvent based: when used indoors, ventilate premises thoroughly. Keep in a cool, dry place.

TEMPERATURE

Storage temperature: between 0° C and 30° C. Must be applied to material at temperatures between 10° and 30° C.

COMPOSITION

Blend of siloxane compounds dispersed in dearomatized hydrocarbon solvent.

LABELLING WARNING: Danger Hazard indication:

Flammable liquid and vapour. May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking.

Caution recommendations:

Caution recommendations:
If medical advice is needed, have product
container or label at hand. Keep out of reach
of children. Keep away from heat / sparks /
open flames / hot surfaces. No smoking. Wear
protective gloves / protective clothing / eye protection
/ face protection. IF SWALLOWED: Immediately call
a POISON CENTER or doctor / physician. Dispose
of contents / container in accordance with official
regulations
Contains: NAPHTA (PETROL.) HYDROTREATED HEAVY

TECHNICAL INFORMATION

Appearance: liquid Colour: colourless

Odour: slight odour of hydrocarbon solvent

Density: 0,874 kg/litre **Flash point:** 40°C

The information above reflects our latest technical know-how and is the outcome of ongoing laboratory research and testing. However, some factors are beyond our control. It is essential to integrate our suggestions with your own on-site preliminary tests and check. Fila accepts no liability for improper use of its products.

DO/LB 14 REV. 00 - 30/05/2012

