



- TERRACOTTA
- QUARRY TILES
- UNPOLISHED MARBLE AND AGGLOMERATES
- CONCRETE



WHAT IT'S FOR

- Stain protection agent for internal and external surfaces.
- Protective basecoat for waxed internal surfaces with rustic or rough finishes.

ADVANTAGES

- Does not alter original colour and appearance.
- No film forming.
- Does not alter terracotta frost resistance: tested by the Bologna Ceramic Centre.
- Certified as suitable for use on food contact surfaces.
- Excellent for sanded rustic terracotta and tumbled marble.

HOW IT'S USED

Do not dilute: Ready to use.

Application:

For treatment of exterior pavings: apply a first coat of **HYDROREP** (for natural stone) or **FILAES82** (for terracotta) to the dry paving. The following day, brush on an even, continuous coat of **FILAFOB**.

For indoor use, apply **FILAFOB** with a large brush. The following day, apply one or two coats of the most suitable protective product (**FILAMATT**, **FILASATIN**, **FILALONGLIFE**)

Maintenance:

diluted solution of **FILACLEANER**.

COVERAGE

With one litre:

Stone	10/20 m²
Terracotta Tuscan, rustic, polished	15/20 m²
Handmade Terracotta hollow tile, brick, spanish	5/10 m²

"Coverage rates are approximate and refer to a single coat of the product"

Packaging

1 litre cans in box of 12.
5 litre cans in box of 4.

PRECAUTIONS

- Keep out of the reach of children.
- Dispose of the container properly after use.
- When used indoors, ventilate the premises thoroughly.

TEMPERATURE

Storage temperature: between 0° C and 30° C.
Must be applied to material at temperatures between 5° and 30° C.

COMPOSITION

Blend of synthetic resins dispersed in de-aromatized hydrocarbon solvent.

LABELLING

WARNING: Danger
Hazard indication:

Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause long lasting harmful effects to aquatic life. Repeated exposure may cause skin dryness or cracking.

Caution recommendations:

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat / sparks / open flames / hot surfaces. No smoking. Wear protective gloves / protective clothing / eye protection / face protection. IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician. Dispose of contents / container in accordance with official regulations.
Contains: ISOALCANI C10-C12



TECHNICAL INFORMATION

Appearance: transparent liquid

Colour: colourless

Odour: distinctive hydrocarbon solvent odour

Density: 0,763 kg/litre

Flash point: 40° C

The information above reflects our latest technical know-how and is the outcome of ongoing laboratory research and testing. However, some factors are beyond our control. It is essential to integrate our suggestions with your own on-site preliminary tests and check. Fila accepts no liability for improper use of its products.